DATA SHEET

TLK 25 Wi-Fi

Wearable Communications Device





Let's TLK

Communicate and operate confidently with TLK 25 Wi-Fi, a wearable WAVE PTX™ device that elevates your push-to-talk capabilities and doesn't limit communication to one location. Compact, powerful, rugged and equipped with an intuitive voice assistant for seamless communications, the TLK 25 is designed for ease of use, efficiency and safety. Access a communications, management and safety ecosystem in a small, intelligent device connected to your Wi-Fi network.



Sleek, smart and safe

- · Lightweight, wearable design
- Durable and discreet
- Shaped for safety



Intuitive voice assistance

- Communications
- Device settings
- · Safety features Lone worker, fall alert
- User and device statuses
- Key Information Personal alert, software updates



Packaged ecosystem

- · Wi-Fi based and flexible
- Safety features Emergency calling, lone worker, fall alert, ambient listening
- WAVE PTX ecosystem











Device specifications

| GENERAL SPECIFICATIONS | | | | | | | |
|--|---|--|--|--|--|--|--|
| Network | 2.4, 5 GHz Wi-Fi | | | | | | |
| Channel Capacity | 96 Channels | | | | | | |
| Contact List | 300 Contacts | | | | | | |
| Dimensions | 82 x 48 x 18.7mm (3.2 x 1.9 x 0.7 in) | | | | | | |
| Weight (with Embedded Battery) | 73g (2.6 oz) | | | | | | |
| Battery Capacity | 1260mAh | | | | | | |
| Battery (Type Battery) Operating Hours 5:5:90 Duty Cycle | 12 hours | | | | | | |
| IP Rating | IP67 | | | | | | |
| Ports | USB Type-C (use for charging) 3.5mm audio jack | | | | | | |
| Sensor | Accelerometer | | | | | | |
| Apps | Powered by WAVE PTX | | | | | | |
| Encryption | AES 256 | | | | | | |

| AUDIO SPECIFICATIONS | |
|--|------------|
| Digital Vocoder Type | OPUS |
| Audio Response | +1, -3 dB |
| Audio Distortion at Rated Audio | <1% |
| Maximum Speech Loudness by Default ¹ | 115 dB SPL |

| WIFI SPECIFICATIONS | | | | | | |
|-----------------------------|--|--|--|--|--|--|
| Frequency Range | 2.4 GHz, 5 GHz | | | | | |
| Standards Supported | 802.11 a, b, g, n, ac | | | | | |
| Security Protocol Supported | WPA2 (personal and enterprise), WPA3 (personal) | | | | | |
| Maximum Number of SSIDs | 5 | | | | | |

| BLUETOOTH | |
|-------------------------------|----------------|
| Version | 5.0 LE |
| Range | Up to 10m |
| Supported Profiles | HSP, SPP, GATT |
| Simultaneous Audio Connection | 1 |

| ENVIRONMENTAL SPECIFICATIONS | | | | |
|------------------------------|---|--|--|--|
| Operating Temperature | -20°C to 60°C (radio) -10°C to 60°C (with battery) | | | |
| Storage Temperature | -40°C to 85°C | | | |
| Thermal Shock | Per MIL-STD | | | |
| Humidity | Per MIL-STD | | | |
| Electrostatic Discharge | Per MIL-STD | | | |
| Dust and Water Intrusion | IP67 | | | |
| Packaging Test | Per MIL-STD | | | |

| MILITARY STANDARDS (MIL-STD-810) | | | | | | | | | | | | |
|----------------------------------|-------------|------------------|-------------|----------------------|--------------|-----------------------|--------------|----------------------|--------------|----------------------|--------------|----------------------|
| | MIL-STD810C | | MIL-STD810D | | MIL-STD 810E | | MIL-STD 810F | | MIL-STD 810G | | MIL-STD 810H | |
| | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure |
| Low Pressure | 500.1 | I | 500.2 | II | 500.3 | II | 500.4 | II | 500.6 | II | 500.6 | II |
| High Temperature | 501.1 | I, II | 501.2 | I/A1, II/A1 | 501.3 | I/A1, II/A1 | 501.4 | I/Hot, II/ Hot | 501.6 | I/A1, II/A1 | 501.7 | I/A1, II/A1 |
| Low Temperature | 502.1 | ı | 502.2 | 1, 11 | 502.3 | I, II | 502.4 | I, II | 502.6 | 1, 11 | 502.7 | I, II |
| Temperature Shock | 503.1 | I | 503.2 | A1/C3 | 503.3 | A1/C3 | 503.4 | I | 503.6 | I-C | 503.7 | I-C |
| Solar Radiation | 505.1 | II | 505.2 | I/A1 | 505.3 | I/A1 | 505.4 | I/A1 | 505.6 | I/A1 | 505.7 | I/A1 |
| Rain | 506.1 | l, II | 506.2 | 1, 11 | 506.3 | l, II | 506.4 | l, III | 506.6 | I, III | 506.6 | I, III |
| Humidity | 507.1 | II | 507.2 | II | 507.3 | II | 507.4 | - | 507.6 | II/ Aggravated | 507.6 | II/ Aggravated |
| Salt Fog | 509.1 | I | 509.2 | I | 509.3 | I | 509.4 | - | 509.6 | - | 509.7 | - |
| Blowing Dust & Sand | 510.1 | I/- | 510.2 | I, II | 510.3 | I, II | 510.4 | I, II | 510.6 | I, II | 510.7 | I, II |
| Vibration | 514.2 | VIII/CatF, XI | 514.3 | I/Cat10, II/ Cat3 | 514.4 | I/Cat10, III/ Cat3 | 514.5 | I/Cat24, II/ Cat5 | 514.7 | I/Cat24, II/ Cat5 | 514.8 | I/Cat24, II/ Cat5 |
| Shock | 516.2 | I, II | 516.3 | I, IV | 516.4 | I, IV | 516.5 | I, IV | 516.7 | I, IV | 516.8 | I, IV |
| Contamination by Fluids | | | | | | | | | 504.2 | II | 504.3 | 2.2.6b |

¹ Loudness performance based on TLK 25 paired with PMLN8536



Wear your TLK 25 the way you want



High quality audio and operational experiences

Badge clip: PMLN8538

Equipped with push-to-talk and voice assistant buttons, the TLK 25 comes with a compatible earpiece that lets users keep their device in their pocket while carrying out essential functions. Additionally, the TLK 25 supports Bluetooth 5.0 LE, offering users the flexibility to use Bluetooth earpieces or headphones for improved range, connectivity, clearer audio, and enhanced power efficiency.

TLK 25 Standard Package (HK2205) Includes: Radio plus Earpiece (PMLN8536), Badge clip (PMLN8538) and optional USB-C to USB-A charging cable (PMKN4294)

Additional available accessories:

Holster: PMLN8537

Short cord earpiece: PMLN8613

USB-C to USB-A charging cable: PMKN4294

Wall plug PS 240V 5VDC/1.5A USB-A for use with PMKN4294 (EURO): PS000150A32 Wall plug PS 240V 5VDC/1.5A USB-A for use with PMKN4294 (UK): PS000150A33

Multi-Unit Charger (MUC) with magnetic device support:

Desktop MUC with PS (EURO): PMPN4662

MUC Wall plug PS 100-240V Fixed blade 12V/5A (EURO): PS000580A02 MUC Wall plug PS 100-240V Fixed blade 12V/5A (UK): PS000580A03



To learn more, visit: www.motorolasolutions.com/tlk25



Sinora Srl

www.sinora.it

+39.0541.694212

marketing@sinora.it



Motorola Solutions UK Limited, Nova South, 160 Victoria Street, London, SW1E 5LB. motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2024 Motorola Solutions, Inc. All rights reserved. 02-2024

